

City of Riverview

14100 Civic Park Drive Riverview, MI 48193-6300

(734) 281-4242 • Fax: (734) 281-4247

BUILDING - RENTAL CHECKLIST

ADDRI	ESS: DATE:
()	REPAIR OR REPLACE CONCRETE / TRIP HAZARDS AS INDICATED: (PERMIT REQUIRED) Sidewalk(s) Driveway Approach Service Walk
()	PORCH(S): FRONT REAR CAP: Repair or Replace Re-install to Code STEPS: Repair Replace Re-install to Code PORCH FOUNDATION: Repair Replace Re-install to Code PORCH GUARDRAIL/HANDRAIL: Install at
()	INTERIOR STEPS: () UPSTAIRS () BASEMENT () OTHER Install handrail to code for: Block open side(s) for: () UPSTAIRS () BASEMENT () OTHER
()	LANDING AREA AT EXTERIOR DOORS: () FRONT () SIDE () REAR Provide a minimum 3' x 3' landing area
()	EXTERIOR DOORS: SCRAPE / PAINT OR REPLACE: () FRONT () SIDE () REAR REPLACE KICK PANEL: () FRONT () SIDE () REAR REPLACE HARDWARE: () LATCH () HANDLE () HINGES DOOR CLOSER – REPAIR: () FRONT () SIDE () REAR LOCK(S): REPLACE DOUBLE-KEY CYLINDER LOCKS TO THUMB-TURN AT:
()	EXTERIOR WALLS / TRIM: () POWERWASH () SCRAPE AND PAIN () REPLACE DAMAGED BRICKS () REPLACE DAMAGED MORTAR – TUCKPOINT () SIDING – REPLACE OR REPAIR () ROTTED WOOD – REPLACE OR REPAIR () TRIM
()	GARAGE: () Demolish () Repair
()	SHED: () Demolish () Repair () Must be on concrete pad
()	ROOF: () Replace () Repair/Replace Missing Shingles () Repair Valley(s)

BUILDING INSPECTION CONT.

	FENCE: Remove, repair, replace or clean
	REPAIR OR REPLACE: () Left Side () Right Side () Rear () All
	YARD:
	TRIM OVERGROWN TREES / BUSHES / PLANTS BACK AT:
	() AROUND FENCE () AROUND HOUSE () AROUND GARAGE/SHED
	REMOVE WEEDS AND DEBRIS AT:
	WINDOWS:
	BROKEN GLASS: REPAIR OR REPLACE AT:
	STORM WINDOWS: REPAIR OR REPLACE AT:
	SCREENS: REPAIR OR REPLACE AT:
	HANDLES: REPAIR OR REPLACE AT:
	LATCHES: REPAIR OR REPLACE AT:
	SWIMMING POOL / HOT TUB:
,	
	PERMIT REQUIRED: () YES () NO
	DRAINAGE: Provide positive drainage by installing gutters, extensions, downspouts at: () Front () Rear () Side(s) () All around house
	ADDITIONAL COMMENTS:

ELECTRICAL

OCATION:	APPLICANT'S NAME:
1.	Increase electrical service to minimum of (3) wire 100 amperes.
2.	Provide a switch controlled light at entrance doorway Front Rear Side
3,	Provide wall switch to control ceiling fixture in
4.	Provide a switch controlled ceiling light or wall light in bathroom.
5.	Provide a switch controlled ceiling light in kitchen.
3. 4. 5. 6.	Provide a switch controlled ceiling light or switch controlled duplex electrical receptacle in: Bedroom(
	Living Room Dining Room Bathroom(s) Recreation Roo
	KitchenOther (specify).
7.	KitchenOther (specify). Provide additional duplex electrical receptacle(s) conveniently located:Bedroom(s)Dining Room
	Bathroom(s) Living Room Kitchen Recreation Room
8.	Install multiple switch control at head and foot of stair to (second floor), (basement) with a lighting outlet so placed
	to adequately illuminate stair.
9.	Install additional lighting outlets in basement so as to provide one lighting outlet per each 200 square feet of floor
	space,
- 10,	Provide a separate wall mounted 20 ampere laundry circuit.
11.	Provide at least one lighting outlet in basement toilet room, basement furnace room, basement utility room
12.	Install correct ampere rated type "s" fuses.
13.	Repair or replace defective electrical receptacle(s), wall switches, wall fixture(s), ceiling fixture(s) in
. 14.	Discontinue use of extension cords in lieu of permanent wiring in
15.	Remove or protect surface wiring located below joists or on walls.
16.	Replace missing cover plates on receptacles and switches in
17,	Provide junction box for open splice wiring in
18.	Replace or remove unapproved wirling in
	Install separate 20 amp. circuit for kitchen, supplying (3) duplex outlets.
20.	Provide separate 15 amp. minimum circuit for furnace.
21,	Jumper water meter with a No. 6 minimum copper conductor using approved ground clamps.
	Remove unused wiring,
	Replace equipment covers.
	Install smoke detector.
	Ground kitchen and laundry outlets, and bathroom outlets.
	Wire pool to code.
	Install G.F.I. receptacle In
SERMII REG	QUIREDFEE: \$
	WORK TO BE DONE BY LICENSED CONTRACTORYESNO.
ADDITIONAL	COMMENTS:
1.	



City of Riverview

14100 Civic Park Drive Riverview, MI 48193-6300

(734) 281-4242 • Fax: (734) 281-4247

PLUMBING - RENTAL CHECKLIST

ADDRE	ESS:DATE:
()	PORCELAIN FIXTURES: Repair, re-glaze, or replace chipped fixtures for:
()	WATER METER: Requires full opening valves on both sides of meter
()	WATER CLOSET REPLACE: () Fixture () Ballcock () Seat () Secure to floor
()	CAULK FLOOR/SURFACE AREAS FOR THE:
()	VACUUM BREAKERS/HOSE BIBBS REQUIRED FOR: () Laundry faucet () Outside faucet
()	FLOOR DRAINS/SCREENS: () Replace missing/broken cleanout plugs () strainers
()	LAUNDRY TUB: () Replace old cement/drum trap units () Secure to floor
()	SADDLE VALVES: Replace saddle valves; replace with tees or valves of approved materials () Humidifier () Ice Maker () Water Filter () Insta-Hot Device () Other
()	SANITARY WASTE LINE: Replace or repair sanitary line:
()	CLEANOUT: Provide, install or restore () Stack base () Bldg drain () Sewer junction
()	WATER LINES: () Replace undersized () Replace deteriorated pipes
()	WATER LINE CONNECTION: Replace iron to copper connections with dielectric unions
()	SHOWER FAUCET: Install vacuum breakers/check valve for handheld shower heads or replace with a fixed shower head.
()	FAUCETS: () Repair/replace leaks and defects: AIR CHAMBERS: () Repair () Kitchen () Bath () Other
()	DRAINS: Replace "S" Trap with "P" Trap FLOOR DRAINS: () Require Strainers/Trap () Kitchen () Bath () Other
()	DISHWASHER DRAIN: Raise the dishwasher discharge piping or hoses and secure to the bottom of the counter-top
()	VENTING: Sanitary venting required for: () Kitchen () Laundry () Vanity Sink () Toilet () Shower () Bathtub () Floor Drain
().	HOT WATER TANK: Replace/Install () Piping () Relief valve () Discharge Piping
()	PERMIT REQUIRED? YESNO
Comm	ients:



City of Riverview

14100 Civic Park Drive Riverview, MI 48193-6300

(734) 281-4242 • Fax: (734) 281-4247

MECHANICAL - RENTAL CHECKLIST

ADDRESS: DATE:		
()	NUMBER OF FURNACE(S): TEST FURNACE HEAT EXCHANGER/FOR SAFETY Furnaces two years or older must have the heat exchanger and furnace safety tested by a licensed contractor. *Copy must be submitted to building department with furnace brand, model number, and serial number.	
()	BOILER: Requires shut-off () Pressure valve () Low water shut-off () Backflow preventer	
()	INSTALL: Lever handle shut-off, union tee in gas line for () Hot water tank () Furnace	
()	INSTALL: Lever handle shut-off in gas line near gas fired appliances () Stove () Dryer	
()	DRYER VENT: Must be 4-inch metal smooth pipe; (No Plastic) and secured with metal tape	
()	RELOCATE: () Gas pipe union () Shut-off outside of furnace	
()	REMOVE NON-CODE TEE: On gas line near	
()	SECURE ALL GAS PIPING FOR (AREA):	
()	CAP OR PLUG OPEN GAS LINES FOR: () Stove () Dryer () HWT () Other	
()	HUMIDIFIER: Remove, repair, replace or clean	
()	PRESSURE RELIEF VENT: Vent with ¾" hard pipe to within 4-inche off the floor for:	
. ()	INCINERATOR: Remove; Cap/Plug gas opening; Cement chimney opening; Weld door shut	
()	SECURE AIR GRILLS (REGISTERS) FOR: () Return air () Supply air	
()	DUCT: REPAIR/REPLACE: () Plenum () Ductwork SECURE: () Return () Supply duct work to joist	
()	BATHROOM VENTING: () Venting required per code	
()	HEAT /RETURN AIR: Heat must be provided to all rooms; Install for	
()	CHIMNEY: () Vent pipes sealed/cemented and have accessible clean-out	
	COMMENTS:	
()	FLUE PIPES: () Proper pitch () Secure with screws at each joint () Replace w/gal. pipe	
()	COMBUSTIBLES: Maintain proper clearance to combustibles for () HWT () Furnace	
()	PERMIT REQUIRED? YESNO	